

DYNAMIC CONTROL OF A FLOW-RACK AUTOMATED STORAGE AND RETRIEVAL SYSTEM

Khalid HACHEMI***, Hassane ALLA*

* Gipsa-Lab, Département Automatique de Grenoble ENSIEG – BP 46 F-38402 St Martin d'Hères
Cedex, France

{khalid.hachemi, hassane.alla@lag.ensieg.inpg.fr}

** IMSI, Université d'Oran and Laboratoire d'Automatique de Tlemcen, Algeria

Abstract: In this paper we propose a control scheme based on coloured Petri net (CPN) for a flow-rack automated storage and retrieval system. The AS/RS is modelled using Coloured Petri nets, the developed model has been used to capture and provide the rack state. We introduce in the control system an optimization module as a decision process which performs a real-time optimization working on a discrete events time scale. The objective is to find bin locations for the retrieval requests by minimizing the total number of retrieval cycles for a batch of requests and thereby increase the system throughput. By solving the optimization model, the proposed method gives according to customers request and the rack state, the best bin locations for retrieval, i.e. allowing at the same time to satisfy the customers request and carrying out the minimum of retrieval cycles.

Keywords: Flow-rack automated storage and retrieval systems, Coloured Petri nets, throughput, retrieval sequencing, optimization.

1. INTRODUCTION

A typical Automated Storage and Retrieval System is composed of storage racks, storage/retrieval (S/R) machines, conveyors and pickup/delivery (P/D) stations. The unit-load AS/RS is considered as the generic form of the others AS/RS. In the unit-load AS/RS, the items are stored and retrieved directly on the face of the rack by the storage/retrieval (S/R) machine. The flow-rack AS/RS is composed of deep bins which can contain several products. Two machines are used; a storage machine with load

items and a retrieval machine for items picking. These machines take place on opposite sides of the rack (storage side and retrieval side). So the items are stored also in-depth, which increases considerably the retrieval time of the products inside the rack. This fundamental difference between the two AS/RS due to in-depth storage induces a great difficulty of study and control. According to literature dealing with AS/RS, throughput system is considered the most important performance.

To achieve this goal, researchers developed several approaches. For a unit-load AS/RS and

using a continuous rack face approximation, Bozer and White [3] developed analytical expressions of travel time for single command cycle (SC) and dual command cycle (DC). They used randomized storage policy under a variety of input/output point and S/R machine dwell point configurations. Other authors were interested in optimal dwell point positioning of S/R machine [4, 7, 11]. However, in a recent paper the authors in [10] conclude, via a simulation study, that the dwell-point strategy has an insignificant impact on the relative system response time when the system is highly utilised. Sari, *et al.* [12] developed closed-form travel time expressions for flow-rack AS/RS. Two approaches are presented; continuous and discrete. The continuous approach is based on a continuous rack face approximation. These expressions are compared, via simulation, with exact models given by the discrete approach. The authors found that there is no significant difference between the results obtained from the two approaches and conclude that the expressions based on continuous approach are easier to calculate and more practical than the discrete approach, which require extensive computation time. Another way to maximize throughput was developed by researchers. They were interested in scheduling methods with sequence retrieval requests processed by the S/R machine in order to reduce the travel time. Generally, the storage requests are processed in first-come-first-served (FCFS) manner since the sequence of items to store present a physical flow where it is difficult to modify the filing (in a conveyor for example), while retrieval request can be re-sequenced because they are just an information flow (list). Lee and Schaefer [9] studied a problem of sequencing retrieval requests in a unit-load AS/RS. In order to reduce the total travel time of the storage/retrieval machine, they introduced a method that finds either optimal or near-optimal solution quickly for moderate size problems. Van den Berg and Gademan [13] were interested in the sequencing of storage/retrieval requests by considering the block sequencing approach, in an AS/RS with dedicated storage. The objective was to find a route of minimal total travel time. The problem was equivalent to the Travelling Salesman Problem; they showed that the particular case of sequencing under a dedicated storage policy can be solved in polynomial time. In [8], the authors proposed new replenishment process logic, according to the customer requests. The role of the replenishment process is to prepare items for

the next picking cycle. The inputs of their replenishment model are demand for the next picking cycle and current pick face (location, product, remaining amount), while the output is the pick face for the next picking cycle (totes that will be replenished and number of compartments for each product type). The objective was to minimize the set-up time.

AS/RS control based on Petri nets received some attention in the literature. Amato, *et al.* [2] developed two algorithms of control for an AS/RS modelled by Coloured Timed Petri Nets. They integrate an optimizer system in the control architecture which performs real-time optimization to improve the throughput system. Dotoli, *et al.* [6] proposed a modular modelling for an AS/RS comprising rail guided vehicles and narrow aisle cranes. They used Coloured Timed Petri Nets and tested several control and management policies to show how the simulated model can help to improve the overall system performance.

In this paper, we develop a dynamic control system for the flow-rack AS/RS and we are interested in the reduction of retrieval cycles, to improve the system throughput. For a flow-rack AS/RS, a requested product can be stored in depth inside the rack, thus the retrieval machine can require more than one retrieval cycle to reach it. Therefore, we are also attached to the reduction of the restoring operations which are very expensive in terms of time consuming. With this intention, we started by modelling the AS/RS using Coloured Petri nets (CPN). We propose then a control and scheduling scheme which exploits the CPN model, as a state observer. The decision rules are generated by an optimization module of the number of retrieval cycles. The paper is organized as follows. The flow-rack system and its operation are described in Section 2. Section 3 exposes the CPN model and its coupling with the optimization module. In Section 4, the mathematical model of the retrieval problem and a case study are presented. Finally, Section 5 gives conclusions.

2. FLOW-RACK AUTOMATED STORAGE AND RETRIEVAL SYSTEM

Gravity flow-rack AS/RS is composed of a deep rack with several bins. Each bin can contain




Fig. 1: Flow-rack structure




Fig. 2: Typical configuration for a flow-rack AS/RS

multiple items placed according to a FIFO rotation. When an item is removed from a bin, the next item automatically rolls to the front of the rack. The rack uses inclined shelves equipped with roll track to move products by gravity from the storage to the picking (retrieval) side of the system. The products are simply loaded into the back of the system (storage side) by the storage machine (SM) and they flow to the front of the system. The products are picked on the retrieval side by the retrieval machine (RM). The storage and retrieval machines can move simultaneously on two axes. These two axes form the plan "xy" parallel with the two sides of the rack. A pickup station is located on the storage side, where the storage machine takes the products to be stored. A drop-off station is located on the retrieval side, where the retrieval machine deposits the products for the delivery. A restoring conveyor inclined in opposite direction, connects the retrieval machine to storage machine. It makes it possible to transfer the products to be restored towards the pickup station. Figure 1, gives the structure of a gravity flow rack used for distribution. In Figure 2, the detailed configuration of a gravity flow-rack AS/RS is shown. The rack is composed of several bins, and each bin has several locations in which the products can be stored. Each location has a storage capacity of one item (product). For example, for retrieving a required product which

is in the fourth location of a bin, the retrieval machine needs initially to retrieve one by one, the three products which precede it, to send them to the restoring conveyor for being reintroduced in the rack. The required product will be deposited in the drop-off station. The rack contains several types of products stored according to a policy of storage.




Fig. 3: Products layout inside the bin

Random storage is considered; i.e. a product can be stored in any location of the rack and a same bin can contain different products types. Given customers requests (the demand), the problem consists in determining bin locations of products satisfying this demand and realizing the minimum number of retrieval cycles.

The request drawing up consists in gathering all customers' requests in only one batch represented by a vector. Each element of this vector represents the sum of item quantities of the corresponding product, resulting from all requests of customers. The resulting request vector C will be equal to:

$$C = \sum_{i,j} q_{ij} \text{ With:}$$

q_{ij} : amount of item j requested by customer i .

q_j : total amount of item j for all customers.

3. STRUCTURE OF CONTROL SYSTEM

3.1 Coloured Petri net model.

Coloured Petri nets (CPN) are derived from ordinary Petri nets and allow to model complex systems with identical sub parts. They constitute an abbreviation. In a CPN, with places are associated identifiers or "colours". For more details, see [5]. In order to represent the dynamics of the flow-rack AS/RS, a coloured Petri net is developed. Indeed, the system is of complex management, owing to the fact that the rack state at every moment can be modified by three different operations: the storage of a new product, the retrieval of a

requested product and possibly the restoring of not requested products. Moreover, the size of the system is significant and it is necessary to take into account move of the products from a location to another inside the bins. The CPN model is shown in Figure 4. At any given moment, the system state is expressed by the CPN marking.




Fig. 4: CPN model of flow-rack AS/RS

The model of Figure 4 represents the bins of the rack like FIFO queues. Indeed, the operation of a bin is similar to a FIFO, owing to the fact that the product which will be introduced first in the bin will leave it first, even if it is led once again to the restoring. The sets of colours which manage the CPN model are:

$P = \{ \prec pi \succ, i \in [1, n] \}$: set of products type.

$F = \{ \prec fk \succ, k \in [1, m] \}$: set of rack bins.

$E = \{ \prec ej \succ, j \in [1, q] \}$: set of bin locations.

The arcs are associated functions. They are defined as follows:

The function u introduces a product pi into the last location of a bin fk .

$$u : P \times F \rightarrow P \times F \times \{eq\}$$

$$(pi, fk) \mapsto u(pi, fk) = \prec pi, fk, eq \succ$$

The function v extracts a product pi from the first location of a bin fk .

$$v : P \times F \rightarrow P \times F \times \{el\}$$

$$(pi, fk) \mapsto v(pi, fk) = \prec pi, fk, el \succ$$

The used functions, related to the arcs are: Id, Prec₃ and Proj₁, such as:

$$\text{Id}(\langle ci \rangle) = \langle ci \rangle$$

$$\text{Prec}_3(\langle c_{i1}, c_{i2}, c_{i3} \rangle) = \langle c_{i1}, c_{i2}, c_{(i-1)3} \rangle \quad [3]$$

$$\text{Proj}_1(\langle c_{i1}, c_{i2}, \dots, c_{im} \rangle) = \langle c_{i2}, \dots, c_{im} \rangle$$

The interpretation of places and transitions of the CPN model is summarized in Table 1.

Place/ Transition	Colours	Interpretation
V	$\langle fk, ej \rangle$	The location ej of the bin fk is empty
W	$\langle pi, fk, ej \rangle$	The location ej of bin fk contains a product of type pi
R	$\langle pi \rangle$	A product of type pi is recycled
Ts	$\langle pi, fk \rangle$	Introduce a product pi in location q of bin fk
Tr	$\langle pi, fk \rangle$	Introduce a recycled product pi in location q of bin fk
Td	$\langle pi, fk \rangle$	Evacuate a product of type pi from location 1 of bin fk towards the drop-off station
Tf	$\langle pi, fk \rangle$	Evacuate a product of type pi from location 1 of bin fk towards the recycling
T	$\langle pi, fk, ej \rangle$	Move a product pi from location j to location $j-l$

Table 1: Interpretation of CPN places and transitions

3.2 Feedback control

Figure 5 shows the AS/RS control based on CPN model. The reference input of the control system is the customers request periodically worked out. The values q_1 to q_n represent the items (1 to n) quantities required after regrouping of the various customers requests. The control system uses feedback from process sensors via the CPN model which acts as state observer. That allows updating the state of the

system after each operation creating a change of state, i.e. retrieval operation, storage operation and restoring operation. The movement of the products from a location to another is very fast and it is of negligible duration compared to those of the storage and retrieval machines. So a product immediately takes the place of the product which precedes it, once released. Another feedback is eventually used to adapt the period of the request processing T_s but will not be detailed here (shown in dotted lines in figure 5).




Fig. 5: Control scheme of the AS/RS

4. OPTIMIZATION BLOCK

The problem consists in satisfying the request of customers (treated by batch) by fulfilling the minimum of retrieval cycles. Indeed, a restoring operation of product is very expensive in consumption of time because it obliges to send back it to be reintroduced in the rack. Consequently, the difference between the access times to the various bins of the rack is not penalizing in terms of the number of retrieval cycles. So, we consider the entire penalty on the depth of the rack. To illustrate the retrieval problem, assume a rack with six bins of four locations each one. Figure 6 represents this rack on a plan x-y. This rack contains three types of products symbolized by \bullet , \blacksquare and \blacktriangle . Assume a customers request, consisting of four products \bullet and two products \blacktriangle . A solution (trajectory) consists in determining a combination of bin locations which satisfies the batch request (Section 2). Two particular solutions are indicated in this figure (S_1 indicated in full line and S_2 in dotted lines). To calculate the total retrieval cost, we calculate initially the cost by product and then we make the sum of costs for all the products. The cost of the product is equal to its depth in the bin. In the case of presence of several products of the trajectory in the same bin, the

cost of all these products is equal to that of the deepest product. So, we will speak about the cost of the bin given by the deepest product. Therefore, the trajectory S_1 has a total cost of: $1 + 2 + 3 + 3 + 4 + 4 = 17$ while that of S_2 is: $3 + 2 + 3 + 3 + 2 = 13$ (only 5 terms appear).




Fig. 6: Retrieval cost according to the selected locations

4.1 Mathematical formulation of the problem

Generally, the data are:

- m bins with q locations each one.
- Products of different types contained in the locations.
- The requested amounts of each product type.

Problem: Determine a trajectory satisfying a request batch (containing the requested products) of minimal total cost.

Criteria: Minimize the sum of the bins costs. This is formalized by Relations 1 - 8.

The rack is presented as a matrix where the lines indicate the indexes of bins and the columns the indexes of locations. The customers order (batch request) is represented by a vector which contains the quantities per type of required products. The problem thus consists in satisfying this demand with the minimum of retrieval cycles of the machine RM. The used parameters are:

k : bin index, $k \in [1, m]$.

j : location index, $j \in [1, q]$

i : product type index, $i \in [1, n]$

S_{kj} : rack state matrix. The elements of this matrix represent the products types stored in their respective locations. In fact, this matrix can be deduced from the marking M of the

CPN model. This marking is updated according to the evolution of the system.

$$M = \begin{bmatrix} m(V) \\ m(W) \\ m(R) \\ m(D) \end{bmatrix}$$

$$S : F \times E \rightarrow P$$

$$(fk, ej) \mapsto S(fk, ej) = pi$$

For each $\langle pi, fk, ej \rangle \in m(W)$: $S(fk, ej) = pi$

$$S(fk, ej) = \phi \text{ otherwise}$$

By just using the indices:

$$S_{kj} = \begin{cases} i, & \text{if } \langle pi, fk, ej \rangle \in m(W) \\ 0 & \text{otherwise} \end{cases}$$

$S_{kj} = 0$, it means that no product is in this

location bin. C : Vector of product type quantities requested by customers,

M_{kj} : is a binary matrix definite as follows:

$$M_{kj} = 0 \text{ or } 1, k = 1 \dots m \text{ and } j = 1 \dots q$$

X_{kj} : is an integer decision matrix definite as follows:

$$X_{kj} = 0 \text{ or } 1, k = 1 \dots m \text{ and } j = 1 \dots q$$

$X_{kj} = 1$, if the location j of bin k is selected for a retrieval. $X_{kj} = 0$, otherwise.

The objective can be formulated as follows:

$$\text{Objective: } \min \sum_{k=1}^m \sum_{j=1}^q M_{kj} * j \quad (1)$$

Subject to

$$\sum_{j=1}^q M_{kj} \leq 1 \quad \text{for each } k \quad (2)$$

$$M_{kj} \leq 1 \text{ if } S_{kj} > 0 \quad \text{for each } k, j \quad (3)$$

$$M_{kj} = 0 \text{ if } S_{kj} = 0 \quad \text{for each } k, j \quad (4)$$

$$\sum_{k=1}^m \sum_{j=1}^q X_{kj} = C_i \text{ if } S_{kj} = i \quad \text{for each } i \quad (5)$$

$$X_{kj} \leq 1 \text{ if } S_{kj} > 0 \quad \text{for each } k, j \quad (6)$$

$$X_{kj} = 0 \text{ if } S_{kj} = 0 \quad \text{for each } k, j \quad (7)$$

$$X_{kj} \leq \sum_{l=j}^q M_{kl} \quad \text{for each } k, j \quad (8)$$

The objective (1) consists in minimizing the retrieval cycles. It minimizes the total depth of products in the rack. Constraint (2) makes it possible to take into account the fact that, if

several products are in the same bin, the depth expressing the number of cycles to be carried out for this bin is equal to the maximum between the products locations indexes in this bin. Constraints (3) and (4) allow to select the possible products locations to be retrieved. Constraint (5) enables to make a complete satisfaction of customers' request. Like constraints (3) and (4), Constraints (6) and (7) define the product locations to be selected but for the decision matrix X . Constraint (8) readjusts the elements of matrix M , in order to allow the calculation of the number of retrieval cycles. Solving this model gives the products locations to be retrieved and the minimal number of retrieval cycles of the machine RM.

4.2 Case study

We consider a rack with $m = 6$; the number of rack bins, $q = 7$; the number of locations in each bin, $n = 10$; the number of the products type in the rack. Since we are interested in optimization of the number of retrieval cycles and for reasons of clarity, the rack is presented with bins arranged vertically. It is an abstract representation, equivalent to the physical representation. Figure 7 represents the rack according to the matrix S considered in this example. The numbers inside the locations are the products types. Therefore,

$$S = \begin{bmatrix} 1 & 2 & 9 & 8 & 4 & 6 & 2 \\ 8 & 10 & 4 & 3 & 4 & 6 & 10 \\ 8 & 6 & 10 & 3 & 10 & 10 & 7 \\ 1 & 4 & 10 & 7 & 7 & 9 & 10 \\ 10 & 2 & 3 & 4 & 10 & 7 & 3 \\ 3 & 1 & 5 & 3 & 7 & 8 & 8 \end{bmatrix}$$




Fig. 7: Rack state with the types of products inside

The customers' request is given in the form of a column vector, as follows:

$$C = [3 \ 3 \ 0 \ 5 \ 0 \ 0 \ 0 \ 0 \ 5]^T$$

This request consists of 3 products of type1, 3 of type 2, 5 of type 4 and 5 of type 10. To create the software model of this optimization problem, we used AMPL language. The model is then solved by CPLEX; solver . After solving of the program using the AMPL/CPLEX system, we obtain the following results:

Objective = 24; it is the number of retrieval cycles to be carried out by the retrieval machine RM. The decision matrix X:

$$X = \begin{bmatrix} 1 & 1 & 0 & 0 & 1 & 0 & 1 \\ 0 & 1 & 1 & 0 & 1 & 0 & 1 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 1 & 1 & 1 & 0 & 0 & 0 & 0 \\ 1 & 1 & 0 & 1 & 1 & 0 & 0 \\ 0 & 1 & 0 & 0 & 0 & 0 & 0 \end{bmatrix}$$

The matrix X , is a decision matrix with binary numbers; they can take either the value 0 or value 1:

0: The product contained in the location and the respective bin is not taken.

1: The product contained in the location and the respective bin is taken.




Fig. 8: Products locations for retrieval

Figure 8 shows the products locations to be retrieved (locations containing value 1) according to the customers order. The control of retrieval machine is thus treated bin by bin according to table 2.

Bin (fk)	Products locations to be retrieved (ej)	Retrieval cycles number
$F1$	$E1, e2, e5, e7$	7
$F2$	$e2, e3, e5, e7$	7
$F3$	No location	0
$F4$	$e1, e2, e3$	3
$F5$	$e1, e2, e4, e5$	5
$F6$	$E2$	2

Table 2: Products locations for retrieval

Note that since the retrieval machine RM, reaches only the first location of each bin, its control consists in making a certain number of retrieval cycles, for each bin. The number of retrieval cycles to carry out c_k (includes the cycles of delivery and the cycles of restoring),

$$\text{for each rack } k \text{ is equal to: } c_k = \sum_{j=1}^q M_{kj} * j$$

Table 3, gives the products locations to be retrieved by type. In this example, we see that the total number of cycles to carry out by the machine RM is equal to 24 cycles and the customers request is made up of sixteen products, So the number of products to be restored is equal to: $24 - 16 = 8$ products. The delivery rate is calculated as follows:

$$\tau_d = \frac{\text{number of delivered products}}{\text{number of retrieved products}} = \frac{16}{24} = 0.67$$

Product Type	Requested quantities	locations to be retrieved (bin, location)
1	3	$(f1, e1), (f4, e1), (f6, e2)$
2	3	$(f1, e2), (f1, e7), (f5, e2)$
4	5	$(f1, e6), (f2, e3), (f2, e5), (f4, e2), (f5, e4)$
10	5	$(f2, e2), (f2, e7), (f4, e3), (f5, e1), (f5, e5)$

Table 3: Products locations for retrieval by type

It means that 67% of retrieval operations are for delivery. The remainder represents the restoring operations. Since the solution of the problem is optimal, this rate is the best delivery rate that it is possible to reach for the customers' request considered here.

5. CONCLUSIONS

In this paper, we have presented a control scheme of a flow-rack AS/RS, based on a coloured Petri net (CPN). The proposed CPN model of the AS/RS, allows to model dynamics of the system and thus to apprehend its complexity. In AS/RS, one of the most important performances is the system throughput. We were interested in minimizing the total number of retrieval cycles and consequently the number of restoring cycles which induce a very expensive processing time. With this intention we have integrated an optimization module as conflict solver, in order to select the products locations to be retrieved in the rack. The optimization problem is formulated in term of integer program. This module exploits the CPN marking to read the rack state. The solution of the problem gives the bin locations to be retrieved for a batch of customers' request and the minimal number of retrieval cycles of the retrieval machine. Note that the advantage of the given optimization method, is that it gives the exact minimal number of retrieval cycles. Thus, the delivery rate of the retrieval machine is maximized and its utilisation rate is minimized, which enables it to function more effectively with a higher system throughput rate. As perspective to this work, we intend to integrate the expiry dates of products in the sequencing problem of retrieval requests where in addition to the minimization of the number of retrieval cycles, it will be necessary to minimize also the risk of products expiry in the rack.

REFERENCES

- [1] Alla , H., Réseaux de Petri Colorés et réseaux de Petri Continus : Application à l'Etude des Systèmes à Événements Discrets. PhD thesis, Institut National polytechnique de Grenoble, France, 1987.
- [2] Amato, F., Basile F., Carbonne, C., An approach to control automated warehouse systems. *Control Engineering Practice*, 13, pp. 1223-1241, 2005.
- [3] Bozer, Y. A., White, J. A., Travel time models for automated storage/retrieval system. *IIE Transactions*, 16, pp. 329-338, 1984.
- [4] Chang, S H., Egbelu, P. J., Relative pre-positioning of storage/retrieval machines in automated storage/retrieval systems to minimize maximum system response time. *IIE Transactions*, 29, pp. 303-312, 1997.
- [5] David, R., Alla, H., *Discrete, Continuous and Hybrid Petri Nets*, Springer, Heidelberg, Germany, 2004.
- [6] Dotoli, M., Fanti, M. P., A coloured Petri net model for automated storage and retrieval systems serviced by rail-guided vehicles: a control perspective. *International Journal of Computer Manufacturing*, 18, n°2-3, pp. 122-136, 2005.
- [7] Egbelu, P.J., Framework for dynamic positioning of storage/retrieval machines in an automated storage/retrieval system. *International Journal of Production Research*, 31, pp. 17-37, 1991.
- [8] Kim, B. I., Heragu, S. S., Graves, R. J., Onge, A. ST., Realization of short cycle time in warehouse replenishment and order picking. *International Journal of Production Research*, 41, pp. 349-364, 2003.
- [9] Lee, H. F., Schaefer, S. K., Retrieval sequencing for unit-load automated storage and retrieval systems with multiple openings. *International Journal of Production Research*, 34, pp. 2943-2962, 1996.
- [10] Meller, R. D., Mungwattana, A., AS/RS dwell-point strategy selection at high system utilization: a simulation study to investigate the magnitude of the benefit. *International Journal of Production Research*, 43, n°24, pp. 5217-5227, 2005.
- [11] Peters, B. A., Smith, J. S., Hale, T.S., Closed form models for determining the optimal dwell point location in automated storage/retrieval systems. *International Journal of Production Research*, 34, pp. 1757-1771, 1996.
- [12] Sari, Z., Saygin, C., Ghouali, N., Travel-time models for flow-rack automated storage and retrieval systems. *International Journal of Advanced Manufacturing Technology*, 25, pp. 979-987, 2005.
- [13] Van den berg, J. P., Gademane, A. J. R. M., Optimal routing in an automated storage/retrieval system with dedicated storage. *IIE transactions*, 31, pp. 407-415, 1999.